ViewSonic® Digital Signage

September / October 2013

With a 25-year heritage as an award-winning display technology leader, ViewSonic is poised to provide the best in complete digital signage solutions. Offering a broad range of product lines and breakthrough technologies, ViewSonic is elevating commercial displays to new levels. Whether you need digital signage for education, business or a commercial installation, ViewSonic has the perfect solution that will change the way you advertise, promote, and broadcast to your target audience. All ViewSonic digital signage solutions come standard with essential features, while individual product lines offer unique options to meet your specific needs.

Media Players

Product	OS	CPU	Graphics	Output Resolution	RAM	Internal Storage	File Support	Network	Connectivity	Mounting (mm)	Dimensions W x H x D (in.)
NMP-570w Wireless Media Player	Linux	–	–	up to 1920 x 1080	–	4GB Storage	Video: MPEG-1/2/4, H.264, VC-1/WMV9 Audio: MPEG-1, MP3 Image: JPEG, PNG	10/100 LAN, WiFi 802.11 b/g/n	HDMI, VGA, A/V out, USB (x2), RJ45, CF card reader	MIS-D100 (VESA® compatible)	5.9 x 4.3 x 1.1
NMP-640 Industrial Media Player	Windows® 7 Home	Intel® Atom™ D525 Duo Core 1.8GHz	NVIDIA GT218 Ion 2	up to 1920 x 1080	2GB DDR-3	320GB HDD	Video: AVC, VC1, MPEG2 Audio: ALC662	Gigabit (10/100/1000 Mbits/sec) LAN	HDMI, VGA, Audio out, Audio in, USB (x4), RJ45, card reader (SD/ SDHC/MS/MS Pro)	VESA® 100 x 100	5.9 X 1.0 X 7.4

Commercial TVs

Product	Screen Size	Resolution	Contrast	Brightness	Video Response	Viewing Angle	Integrated Speakers	VESA® Mount (mm)	Connectivity	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
VT1601LED HDTV	15.6" LED	1366x768 16:9 ratio	500:1	220 cd/m² (typ)	8ms (typ)	90° H 50° V	2.5W (x2)	75x75	HDMI, CVBS, VGA, USB, YPbPr	3.3 lb (w/ stand) 2.9 lb (w/o stand)	15.4 x 11.5 x 4.7 (w/ stand) 15.4 x 10.3 x 1.6 (w/o stand)	18W (typ)	Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Remote, Dolby® Digital Sound, HDTV built-in w/ QAM TV Tuner
VT2215LED HDTV	21.5" LED	1920x1080 Full HD	1,000:1	250 cd/m² (typ)	5ms (typ)	170° H 160° V	3W (x2)	100x100	HDMI, CVBS, VGA, USB, YPbPr	8.2 lb (w/ stand) 7.7 lb (w/o stand)	20.4 x 14.9 x 6.4 (w/ stand) 20.4 x 13.1 x 1.8 (w/o stand)	27W (typ)	Hospitality Menu, USB cloning feature, Progressive Scan, 3D Comb filter, Remote, Dolby® Digital Sound, HDTV built-in w/ QAM TV Tuner
VT2405LED HDTV	23.6" LED	1920x1080 Full HD	1,000:1	300 cd/m² (typ)	5ms (typ)	170° H 160° V	5W (x2)	200x100	Composite, Component, 3.5mm mini stereo, HDMI, DVI, RS-232	10.3 lb (w/ stand) 9.8 lb (w/o stand)	22.1 x 16.2 x 8.5 (w/ stand) 22.1 x 14.0 x 1.5 (w/o stand)	28W (typ)	RS-232 Control Port with IR, HDMI x3, SRS TruSurround® Sound, Hospitality programming, USB cloning feature

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

For the most current product accessories and specifications, visit ViewSonic.com. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16695-03B-08/13]

ViewSonic® See the difference®

Large Format Displays

Product	Screen Size	Brightness	Contrast	Video Response	Viewing Angles	Resolution	Connectivity	Integrated Speakers	VESA® Mount (mm)	Net Weight	Dimensions W x H x D (in.)	Power Usage	Special Features
CDP3235 LCD Display	32"	450 cd/m²	4,000:1	6.5ms	178° H 178° V	1366 x 768	YPbPr, HDMI, DVI, VGA, S-Video, CVBS, RS-232	10W (x2)	400 x 200 200 x 200	33.0 lb (w/ stand) 32.2 lb (w/o stand)	30.4 x 24.5 x 9.4 (w/ stand) 30.4 x 23.0 x 4.5 (w/o stand)	140W (typ)	Loop through (VGA, RS-232), On/Off scheduling, video wall up to 5 x 5
CDE3200-L LED Display	32"	300 cd/m²	3,000:1	6.5ms	170° H 170° V	1920 x 1080 Full HD	HDMI (x3), YPbPr, Component, VGA, S-Video, CVBS, SPDIF, USB, RS-232	10W (x2)	200 x 100	16.1 lb (w/ stand) 14.3 lb (w/o stand)	29.5 x 19.6 x 7.1 (w/ stand) 29.5 x 16.5 x 3.1 (w/o stand)	38W (typ)	Hospitality Menu, RS-232, USB cloning feature, Progressive Scan, IR Pass Through
CDE4200-L LED Display	42"	350 cd/m²	3,000:1	6.5ms	170° H 170° V	1920 x 1080 Full HD	HDMI (x3), YPbPr, Component, VGA, S-Video, CVBS, SPDIF, USB, RS-232	10W (x2)	200 x 200	27.8 lb (w/ stand) 26.2 lb (w/o stand)	38.4 x 26.7 x 8.2 (w/ stand) 38.4 x 24.6 x 2.5 (w/o stand)	59W (typ)	Hospitality Menu, RS-232, USB cloning feature, Progressive Scan, IR Pass Through
CDP4635-T LCD Touch Display	46"	400 cd/m²	4,000:1	8ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, Component, VGA, S-Video, RS-232	10W (x2)	400 x 200 200 x 200	83.8 lb (w/ stand) 69.7 lb (w/o stand)	43.0 x 26.8 x 13.0 (w/ stand) 43.0 x 25.4 x 5.2 (w/o stand)	220W (typ)	Intel® OPS ready, 4 Point optical touch, Loop through (VGA, RS-232)
CDX4650-L LED Display	46"	700 cd/m²	4,000:1	6.5ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, Component, VGA, S-Video, CVBS (BNC)	10W (x2)	400 x 400	58.3 lb (w/ stand) 53.5 lb (w/o stand)	40.2 x 24.2 x 12.9 (w/ stand) 40.2x22.7 x 5.0 (w/o stand)	220W (typ)	Intel® OPS ready, Ultra thin 2.7mm bezel, Video wall up to 10 x 10,
CDP4737-L LED Display	47"	450 cd/m²	1,300:1	12ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, DP, Component, VGA, CVBS (BNC)	–	400 x 400	41.7 lb (w/ stand) 38.6 lb (w/o stand)	39.0 x 25.4 x 11.7 (w/ stand) 39.0 x 25.5 x 1.5 (w/o stand)	120W (typ)	120Hz LED panel, Video wall up to 5 x 5, Built-in Media Player TAA Compliant
CDP5537-L LED Display	54.6"	450 cd/m²	1,300:1	12ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, DP, Component, VGA, CVBS (BNC)	–	400 x 400	51.2 lb (w/ stand) 48.1 lb (w/o stand)	50.5 x 32.5 x 11.7 (w/ stand) 50.5 x 29.6 x 1.5 (w/o stand)	140W (typ)	120Hz LED panel, Video wall up to 5 x 5, Built-in Media Player TAA Compliant
CDX5550-L LED Display	54.6"	700 cd/m²	3,500:1	12ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, Component, VGA, S-video, CVBS (BNC)	10W (x2)	400 x 400	84.2 lb (w/ stand) 79.4 lb (w/o stand)	47.9 x 29.0 x 15.8 (w/ stand) 47.9 x 27.0 x 5.0 (w/o stand)	220W (typ)	Intel® OPS ready, Ultra thin bezel, Video wall up to 10 x 10
CDE6501LED LED Display	65"	360 cd/m²	4,000:1	9ms	178° H 178° V	1920 x 1080 Full HD	HDMI (x3), DVI, Component, VGA, S-Video, CVBS, SPDIF, USB, RS-232	8W (x2), 15W Bass	400 x 400	110.2 lb (w/ stand) 99.2 lb (w/o stand)	60.4 x 39.0 x 11.8 (w/ stand) 60.4 x 36.4 x 1.9 (w/o stand)	240W (typ)	Hospitality Menu, RS-232 loop throught, USB cloning feature, Progressive scan, IR pass through
CDP6530 LCD Display	65"	500 cd/m²	5,000:1	8ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, Component, VGA, S-Video, RS-232	5W (x2)	400 x 400	155.5 lb (w/ stand) 154.3 lb (w/o stand)	59.9 x 40.4 x 16.4 (w/ stand) 59.9 x 35.5 x 5.4 (w/o stand)	520W (typ)	Intel® OPS ready, Video wall up to 10 x 10, Loop through (VGA, RS-232) TAA Compliant
CDP6530-T LCD Touch Display	65"	450 cd/m²	5,000:1	8ms	178° H 178° V	1920 x 1080 Full HD	HDMI, DVI, Component, VGA, S-Video, RS-232	5W (x2)	400 x 400	155.5 lb (w/ stand) 154.3 lb (w/o stand)	59.9 x 40.4 x 16.4 (w/ stand) 59.9 x 35.5 x 5.4 (w/o stand)	520W (typ)	Intel® OPS ready, Dual optical touch, Video wall up to 10 x 10, Loop through (VGA, RS-232) TAA Compliant

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

For the most current product accessories and specifications, visit ViewSonic.com. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16695-03B-08/13]

ViewSonic® See the difference®

Free Standing ePosters

Product	Screen Size	Resolution	Touch	Interface	Connectivity	Internal Storage	File Type Supported	Integrated Speakers	OS Support	Dimensions W x H x D (in.)	Special Features
EP4220 Single Sided ePoster	42"	1920 x 1080 Full HD	–	USB 2.0 (full speed), USB 1.1 port HID compliant	HDMI, VGA, RS-232, PC Audio	2GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	2.5W (x2)	–	27.0 x 72.2 x 17.7	1-year limited warranty with extended options available
EP4610 Single Sided ePoster	46"	1920 x 1080 Full HD	–	USB 2.0 (full speed), USB 1.1 port HID compliant	HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail	4GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	5W (x2)	–	27.8 x 76.8 x 19.5	1-year limited warranty with extended options available
EP4646 Dual Sided ePoster	46"	1920 x 1080 Full HD	–	–	HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail	4GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	5W (x2)	–	27.8 x 76.8 x 19.7	Dual sided display, 1-year limited warranty with extended options available
EP5502 Single Sided ePoster	55"	1920 x 1080 Full HD	–	–	HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail	4GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	5W (x2)	Windows® 7 / 2000 / XP / Vista	32.7 x 78.7 x 17.7	1-year limited warranty with extended options available
EP5502T Single Sided ePoster	55"	1920 x 1080 Full HD	Yes 4096 x 4096 dots	USB 2.0 (full speed), USB 1.1 port HID compliant	HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail	4GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	5W (x2)	Windows® 7 / 2000 / XP / Vista	32.7 x 76.8 x 17.7	Interactive touch screen, 1-year limited warranty with extended options available
EP5555 Dual Sided ePoster	55"	1920 x 1080 Full HD	–	USB 2.0 (full speed), USB 1.1 port HID compliant	HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail	4GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	5W (x2)	–	32.7 x 76.8 x 18.3	Dual sided display, 1-year limited warranty with extended options available
EP5555T Dual Sided ePoster	55"	1920 x 1080 Full HD	Yes, one side 4096 x 4096 dots	USB 2.0 (full speed), USB 1.1 port HID compliant	HDMI, VGA, YPbPr, USB, A/V, RJ45 pigtail	4GB storage	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, Photo: JPEG Audio: WMA, MP3, M4A	5W (x2)	Windows® 7 / 2000 / XP / Vista	32.7 x 76.8 x 18.3	Dual sided display, Interactive touch screen, 1-year limited warranty with extended options available

For the most current product accessories and specifications, visit ViewSonic.com. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16695-03B-08/13]

Mountable ePosters

Product	Screen Size	Resolution	Touch	Interface	Connectivity	Internal Storage	File Type Supported	Integrated Speakers	Mounting (mm)	Dimensions W x H x D (in.)	Special Features
EP1020r Single Sided ePoster	10.4"	800 x 600	–	–	USB, RJ45	2GB CF card	Photo: JPEG Audio: MPEG1, LPCM	3W (x2)	75 x 75	9.9 x 7.8 x 1.7	Signage Manager Express software, 1-year limited warranty with extended options available
EP2203r Single Sided ePoster	21.5"	1920 x 1080 Full HD	–	–	VGA, HDMI, USB	4.0GB	Photo: JPEG, GIF, PNG, BMP Video, MPEG 1/4, WMV, H.264, AVI, FLV	2W (x2)	VESA® 100 x 100	14.9 x 23.1 x 1.3	Slim design, 1-year limited warranty with extended options available
EP3203r Single Sided ePoster	31.5"	1366 x 768	–	–	VGA, HDMI, USB	4.0GB	Photo: JPEG, GIF, PNG, BMP Video, MPEG 1/4, WMV, H.264, AVI, FLV	5W (x2)	VESA® 400 x 200	19.7 x 31.9 x 1.6	Slim design, 1-year limited warranty with extended options available
EP4203r Single Sided ePoster	42"	1920 x 1080 Full HD	–	–	VGA, HDMI, USB	4.0GB	Photo: JPEG, GIF, PNG, BMP Video, MPEG 1/4, WMV, H.264, AVI, FLV	2W (x2)	VESA® 400 x 400	25.0 x 41.0 x 1.6	Slim design, 1-year limited warranty with extended options available

Glossary

LED
LED backlighting enhances display performance, delivers an outstanding color range, and adjusts contrast ratios for remarkably detailed images. The LED backlighting further conserves up to 25%* more energy when compared to conventional displays.

TAA Compliance
Compliant with the Trade Agreement Act (TAA), our broad line of qualifying products are ideal for use in government, educational and corporate environments. TAA-compliant monitors support GSA Schedule needs within the Federal Government.

OPS (Open Pluggable Specification)
The Open Pluggable Specification (OPS) helps standardize the design and development of digital signage media player devices. ViewSonic OPS-ready digital signage displays provide the flexibility for customers to configure and integrate cable-free OPS-compatible media players with performance that meets the application requirements.

Warranty
ViewSonic is committed to using the highest grade panels and offers the industry's leading pixel performance policy. We also back our displays with a 3-year limited warranty for your peace of mind. Optional extended warranties are available for up to 5-years of coverage.

Optical Touch
Optical touch utilizes two or more image sensors that are usually placed around the edges of a display. Unlike Projected Capacitive touch, however, optical touch does not require a conductive object for touch recognition, making it ideal for high-traffic environments where simple finger touch solutions are needed.

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

For the most current product accessories and specifications, visit ViewSonic.com. Program, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16695-03B-08/13]

ViewSonic® See the difference®